


SQUARE/SPOT LIGHT/MEDIUM/BOX/TWIN HEADS/TILTABLE

Model: SR-DL3233



Cutout: 190x100mm

5-25mm

Feature:

- TWIN head square grilled downlight
- Gimble tilt 30 degree
- Compact design with IP54

Technical data:

- Light source COB or others
- LED Power (max) 9W x 2 (250mA x 2, 36V)
- System Power (ref.) 11W x 2 (ref. only depends on the ECG)
- Lumen flux (typ.) 1200lm
- Colour temperature 2700K, 3000K, 4000K
- Colour rendering index Ra \geq 90
- MacAdam Step 3
- Beam Angle 24D, 36D, 45D PMMA Lens
- Tilttable Yes
- Ingress protection IP54
- Operation temperature 0-40C
- Protection Class III
- LED Life time 50,000h L70B10
- Finishing White/Black
- Construction Aluminum
- Installation Ceiling Recessed, spring type
- Dimension 200x110mmx52mm(H)/Cutout 190x110mm
- LED Driver Remote
- Trimless version Yes, Please contact us in detail

Electronic control gear

NON-DIM/Dimmable

MP series

1-10V/0-10V/DALI

SC series

Other brand is available upon request

Light Distribution For 2700K
wide 43°

h(m)	E(lx)	ø(m)
1	2517	ø0.78
2	629.2	ø1.57
3	279.6	ø2.36
4	157.3	ø3.15
5	100.7	ø3.94

****The specification is subject to change without notes.****