

TRACK/SPOT LIGHT/ANTI-GLARE/SNOOT

Model: TRA TR3050



Feature:

- Spot light, track light
- 4 ways track adaptor with build in LED Driver
- High lumen output

Technical data:

- Light source COB or others
- LED Power (max) 12.6W (350mA, 36V)
- System Power (ref.) 15W (ref. only depends on the ECG)
- Lumen flux (typ.) 1100lm
- Colour temperature 2700K, 3000K, 4000K
- Colour rendering index Ra \geq 90
- MacAdam Step 3
- Beam Angle 24D, 38D, 60D Reflector
- Tilttable Yes
- Ingress protection IP21
- Operation temperature 0-40C
- Protection Class III
- LED Life time 50,000h L70B10
- Finishing White/Black
- Construction Aluminum
- Installation Track
- Dimension 75mm(OD) x110mm(H)
- LED Driver Build in track LED driver
- Trimless versiob NA

Electronic control gear

Build in track On/Off LED Driver
(Dimmable LED Driver is on request)

Light Distribution For 3000K

medium 27°			wide 34°		
h(m)	E(lx)	ø(m)	h(m)	E(lx)	ø(m)
1	9092	ø0.49	1	6636	ø0.61
2	2273	ø0.99	2	1659	ø1.22
3	1010	ø1.48	3	737.4	ø1.84
4	568.2	ø1.98	4	414.8	ø2.45
5	363.7	ø2.47	5	265.5	ø3.06

****Accessories: Honeycomb louvre****

****The specification is subject to change without note.****

